

# New, Used, and Surplus Broadband Equipment

## Radio Waves SEC-25V-180-13



**List**                    **\$ 890**  
**Selling Price**       **\$ 507**

One brand new, 3 used.

### Product Description

SEC25V18013 2.4-2.7 GHz, 13 DBI GAIN, SECTOR, N(F), VERTICAL

### Technical Specifications

alpha frequency	2.4 GHz
gain	13 dBi
frequency (bandwidth)	2.4-2.7 GHz
VSWR	<1.5:1
connector	N(F)
wind survival w/o ice (MPH)	125 MPH
vertical beamwidth (deg)	8 deg
horizontal beamwidth (deg)	180 deg
front-to-back ratio (dB)	20 dB
mounting hdw. included (Y/N)	Y
maximum power input (W)	50W
polarization	vertical
lightning protection	N/A
Depth	13"
Height	44"
Weight	18 LB
Warranty	5 years
Shipping *	Parcel Freight

# 2400 LT Series Antennafier™: 2.4GHz Tunable 0.5W-4W AGC WLAN Amplifier (802.11b/g)


**New**                    **\$ 449**

**Selling price \$ 356**

4 used all with 4 year warranty left

[Indoor WiFi Amplifier](#) | [Outdoor WiFi Amplifier](#) | [Description](#) | [Applications](#)

Data Sheets:  [2400LT Series 2.4GHz WLAN Amplifier](#)

Instruction Manuals:  [2400 LT Series Installation Guide](#)

Software:  [Tunable Amplifier Software Ver 1.4](#)

## FEATURES

- Microprocessor controlled "Intelligent Amp™"
- Field Adj. TX & RX Gain via USB & GUI
- Adj. Power Output: 500mW to 4W with AGC
- Adj. Receive Gain: +5 thru +20dB
- High Q 6 Poles of Filtering in RX
- Low 2.5dB RX Noise Figure
- Low Transmit Harmonics
- Durable Powder Coated Aluminum Chassis
- Standard N Type Female Connectors
- Internal Lightning Protection
- 2 Year Product Warranty



2400 LT Series 2.4GHz WLAN Tunable Amplifier



## 2400 LTE Series Antennafier™ Indoor WiFi Amplifiers

**802.11b/802.11g Indoor "WLAN Intelligent Amplifier™" with +12VDC Power Supply & Mtg Bracket**





## UBIQUITI XTREMERANGE2



Item# XR2

**New**  
**Selling price**

**\$ 99.95**  
**\$ 82.72**

**6 Used**

[Add to cart >>>](#)

### Product Description

MINI-PCI ADAPTER 802.11b/g 600mW

[Click here to view data sheet](#)

The XtremeRange series of radio modules by Ubiquiti leverages our strong knowledge and experience gained from customer interactions, field performance evaluations, and lab research; and improves upon the original and highly successful SuperRange series of high-performance 802.11 radio cards. The XtremeRange2 represents the first true carrierclass 802.11b/g-based 2.4GHz radio module specifically designed for mesh, bridging, and infrastructure applications requiring the highest levels of performance and reliability without compromise.

- 600mW 802.11b/g Power
  - -97dBm Rx sensitivity
  - MMCX connector
  - 5/10/20/40 MHz Channels
  - Atheros 5006 chipset based
-

---

## LAIRD POE-48i



Item# POE-48i

**New**  
**Selling Price**

**\$ 22.95**  
**\$ 18.77**

**6 Brand New**

[Add to cart >>>](#)

### Product Description

48V POE ADAPTER WITH POWER CORD

[Click here to view data sheet](#)

The POE-48i is an advanced power supply / power inserter. The power supply is autoranging on the input and has a regulated voltage output. It has overload and short circuit protection in addition to Ethernet surge suppression built-in. The POE-48i is not a proprietary unit. It will function with any equipment which is compliant with the IEEE 802.3af POE standards. For all "i" models the power is supplied on ethernet pins 4/5 (V+) and 7/8 (V-). For the "iR" models the power is supplied on ethernet pins 4/5 (V-) and 7/8 (V+). The POE-48i comes complete with a standard North American 115VAC power cord. International cords are available upon request. A Current Indicator (-CI) model is available. The LED will be AMBER until >35mA current flows to the end device which will turn the LED to GREEN. This is a good way to remotely monitor the connection between the POE and the end device and indicate that the end device is turned on. To order this model add a "-CI" suffix to the standard part number.

Using power over ethernet to power remote devices has several advantages including:

- The power supply can be centrally located where it can be attached to an uninterruptible power supply.
- The user has the ability to easily power on reset the attached equipment from a remote location.
- There is no need to run additional power cabling to the device as power can be supplied over the CAT5 ethernet cable.

---


**WRAP-BOX 2 ANTENNAS, 1 ETHERNET**



Item# WRAP-BOX2A1E

**New** \$ **54.95**  
**Selling Price** \$ **37.00**

**3 New and 3 Used**

 Add to cart >>>

### **Product Description**

WRAP-BOX OUTDOOR WIRELESS ENCLOSURE

[Click here to view data sheet](#)

- Native support for ALIX.3x boards
  - Native support for nano-ITX boards
  - Other boards types require mounting plate
  - Die-Cast Aluminum, NEMA 67 rating
  - 2 waterproof N-type Antennas option
  - 1 waterproof, quick disconnect RJ-45 connector
  - 3 point silicone-rubber gasket
  - Pole-top and wall-mount mounting options
  - OEM brand can be applied in front (serial & ID in the back)
  - ROHS compliant
  - WRAP-BOX-2A1E
- 

## **Telecom Product Profiles**

**765-427-5827**

**dana@telepp.com**